

AMPROBE DIGITAL MULTIMETERS

References : 15XP-A, 35XP-A, 5XP-A



Easy replacement of batteries and fuses

Complete digital multimeters with compact dimensions.

VolTect™ function (non-contact voltage detection)

Magn-Grip case: magnetic suspension strap

Cert. EN 61010 safety, Cat III / 300V, Cat II / 600V

5XP-A:

- 27 ranges
 - 10 functions
 - Recording of Min / Max values
- 15XP-A:
- Automatic ranges
 - Reclining feet
 - TTL logic test
 - Resistance measurement up to 2,000 MΩ
- 35XP-A:

- Temperature measurement up to 1000 ° C
- Measurement of capacity
- Frequency measurement

Reference	15XP-A	35XP-A	5XP-A
DC voltage	200 mV, 2 V, 20 V, 200 V, 1 000 V	400 mV, 4 V, 40 V, 400 V, 1 000 V	200 mV, 2 V, 20 V, 200 V, 1 000 V
AC voltage	200 mV, 2 V, 20 V, 200 V, 750 V	400 mV, 4 V, 40 V, 400 V, 750 V	200 mV, 2 V, 20 V, 200 V, 750 V
AC / DC current	200 µA, 2 mA, 20 mA, 200 mA, 2A	400 µA, 4 µA, 40 mA, 400 mA, 2A	200 µA, 2 mA, 20 mA, 200 mA
Resistance	200 Ω, 2 kΩ, 20 kΩ, 200 kΩ, 2 MΩ, 20 MΩ, 2 000 MΩ	400 Ω, 4 kΩ, 40 kΩ, 400 kΩ, 4 MΩ, 40 MΩ	200Ω, 2kΩ, 20kΩ, 200kΩ, 2MΩ, 20MΩ
Contactless voltage	70 V à 600 VAV (50 Hz à 60 Hz)	70 V à 600 VAV (50 Hz à 60 Hz)	70 V à 600 VAV (50 Hz à 60 Hz)
Capacity		4 nF, 40 nF, 400 nF, 4 µF	
Frequency		4 kHz, 40 kHz, 400 kHz, 1 MHz	
Temperature		-20°C à 1 000°C	
Logic test	TTL, 20 MHz		
Battery test			1,5 V, 9 V
Power supply	1 x 9 V, IEC 6LR61	1 x 9 V, IEC 6LR61	1 x 9 V, IEC 6LR61
Dimensions / Mass:	155 x 72 x 32 mm / 210 g	155 x 72 x 32 mm / 210 g	155 x 72 x 32 mm / 210 g