

MONO-CYCLE DEMINERALISATION UNIT

References : UNIDEMIN, UNIDEMIN2, UNIDEMIN3



Unit supplied with 14 litres of resin (E200)

Regenerable resin

Mono-cycle E100 demineralisation unit (8 litres of resin) or E200 (14 litres) - Instantaneous flow rate of 80 L/hour

Réf : UNIDEMIN2

Unit supplied with 22 litres of resin (E300)

Regenerable resin

Mono-cycle E100 demineralisation unit (8 litres of resin) or E200 (14 litres) - Instantaneous flow rate of 80 L/hour

Réf : UNIDEMIN3

Unit supplied with 8 litres of resin (E100)

Resin can be regenerated

E100 single cycle demineralisation unit - 8 litres of resin

- Instant flow of 80 L / hour
- Large production capacity (about 700 litres of exchange capacity at 20° F of total mineralisation)
- Resin can be regenerated (send us your saturated resin)
- Scalable according to needs: switch to a cylinder of bigger volume (the accessories remaining the

same)

- No water storage, zero discharge
- Set comes with resin cartridge (8 litres), a mini-controller, an S2 cap, a measuring probe, a stainless steel dispensing gun and a connecting pipe of 1.60 m

Réf : UNIDEMIN