

# MULTI-RISK CABINETS - 30 MINUTES

References : 3034M2, 3034M4, 3032M11, 3035M12, 3035M13, 3035M11, 3035M22



## Conformity:

- Tested and approved for 30 minutes according to EN 14470-1 (04/2004) and EN 1363-1 (06/2000).
- Tested and approved for 10 minutes at FM 6050

- Standardised pictograms

### Advantages:

- Fire resistance of 30 minutes according to ISO 834 standardised curve.
- Suitable for all types of chemicals commonly used in the laboratory and industry.
- Separation by groups of dangerous products in accordance with the French Public Health Code and the recommendations of the INRS.
- Base with cover allowing easy movement by pallet truck (empty).
- Automatic thermal fuse closure
- Passive safety:
- Construction in insulating panels, high resistance to chemicals
- Light grey frame RAL 7035; yellow plated fields RAL 1023.

- Markings with standardised symbols.
- Height-adjustable retention shelves.
- Removable retention tray at the bottom.

Active safety:

- Ø 100 mm ventilation holes for possible connection.
- Swing doors with automatic closing and lockable at 3 point
- System for holding door in open position with automatic closing in case of fire.
- Jack feet for levelling.

Options (please contact your regional consultant):

- Additional retention shelf.
- Grating for retention tray (allows extra storage).
- Sliding drawer/retention tray.
- Shelving and PVC retention tray

Under-bench cabinet - 2 doors, 2 compartments

**Réf : 3032M11**

Upper cabinet - 1 doors, 2 compartments

**Réf : 3034M2**

Upper cabinet - 1 doors, 4 compartments

**Réf : 3034M4**

Upper cabinet - 2 doors, 2 compartments

**Réf : 3035M11**

Upper cabinet - 2 doors, 3 compartments

**Réf : 3035M12**

Upper cabinet - 2 doors, 4 compartments

**Réf : 3035M13 - 3035M22 -**

Reference	External dim. H x W x D (mm)	Steel retention shelves	Steel retention tray	Grating for steel tray	Shelving and PVC retention tray	Mass (Kg)
3032M11	635 x 1115 x 630	-	2	2	Option	108
3034M2	1980 x 605 x 550	4	2	Option	Option	126
3034M4	1980 x 605 x 550	-	4	4	Option	142
3035M11	1980 x 1115 x 550	6	2	Option	Option	232
3035M12	1980 x 1115 x 550	7	3	Option	Option	241

3035M13	1980 x 1115 x 550	6	4	Option	Option	244
3035M22	1980 x 1115 x 550	8	4	Option	Option	252