

TEACHER BENCH EQUIPPED WITH A DOUBLE TAP

References : LBPPST02, LBPPGR01, LBPPM02, LBPPGR02, LBPPST01, LBPPM01



Prices include delivery excluding assembly and installation. For installation and connection, consult us.

Please specify the which side is the casing

Main Features PPH tank 500 x 400 x P300 (int) Double cold water tap Frame

The supporting feet are made of square steel tube of 30 x 30 mm. They are equipped with levelling jacks with a floor mounting plate. The front and rear strips are made with a C-profile (120 x 23) mm and ensure perfect flatness and rigidity of the worktop. All the metal elements constituting the frame are protected by a paint based on epoxy resin (23 colours available, see colour chart), cured and resistant to chemical attack. Fluid protection units and backsplashes are made of white melamine.

Worktops

Compact laminate: self-supporting 16 mm, rot-proof phenolic resin covered with white melamine.

Glazed enamel: Tempered glass, 6 mm thick, enamelled on the underside, glued on a melamine-coated, 22 mm thick water-repellent backing.

Sandstone: 8 mm thick matte white enamelled stoneware tile, sealed with cement on a 22 mm thick melamine-coated waterproof backing. The tiles are of 75 x 60 cm. dimensions The seals between the tiles are made of grey thermosetting antacid cement. The edges of the worktop are protected by a PVC edge preventing any impact on the edge of the tiles (protection of the glassware).

Casings

Plumbing

- Outlet: tube with 40 mm female socket, connection at 200 mm from finished floor or podium.

- Cold water, hot water, gas: male stop valve 15/21, connection 300 mm from finished floor or podium.
Electricity
230 V: 1 3 x 2.5 mm². cable
Length of connection 1.5.