

# TOUPCAM EYEPIECE CAMERA

References : TOUPCAM12MP, TOUPCAM1.3MP, TOUPCAM2MP, TOUPCAM5MP, TOUPCAM8MP



## Toupcam, it's so compact!

This USB digital eyepiece camera is inserted in place of a standard optical eyepiece (Ø 23.2 mm). It allows an observation on the screen of your PC, and the recording of images with its software. The installation and the connection of the camera are very simple.

Comes with:

- USB cable 1.5 m
- Two adapters - Ø 30mm - Ø 30,5 mm (for stereo microscopes)
- Software and drivers

Reference	sensor (sCMOS) and size	Pixel (µm)	Sensibility	Resolution
TOUPCAM1.3MP	1/3" (4.60x3.70)	3.6x3.6	NA	1,3 Mp 1024x768
TOUPCAM2MP	1/2.8" (5.73x4.30)	2.9x2.9	73dB	2 Mp 38@960x540
TOUPCAM5MP	1/2.5"(5.70x4.28)	2.2x2.2	18.8ke-/lus	5 Mp 30@2592x1944
TOUPCAM8MP	1/2.5"(6.22x3.50)	1.62x1.62	236mV	8 Mp 30@3840x2160
TOUPCAM12MP	1/2.3"(5.95x4.71)	1.55x1.55	250LSB	12 Mp

1.3 Mp

**Réf : TOUPCAM1.3MP**

2 Mp

**Réf : TOUPCAM2MP**

5 Mp

**Réf : TOUPCAM12MP - TOUPCAM5MP -**

8 Mp

**Réf : TOUPCAM8MP**

Referen ce	Resoluti on	Sensor type	Sensitivi ty (V / Lux-sec at 550 nm)	Dimensi ons	Weight	Utilisati on	Output type	Fixation type	Exploita tion des données
TOUPCAM 1.3MP	1.3 Mp	sCMOS 1/3"		2.72 x 4 cm	12 g	Microscop y	USB	Eyepiece	Software included
TOUPCAM 12MP	12 Mp	sCMOS 1/2.3"	250 LSB	2.72 x 4 cm	12 g	Microscop y	USB	Eyepiece	Software included
TOUPCAM 2MP	2.0 Mp	sCMOS 1/2.7"	3.3	2.72 x 4 cm	12 g	Microscop y	USB	Eyepiece	Software included
TOUPCAM 5MP	5,0 Mp	sCMOS 1/2.5"	18.8	2.72 x 4 cm	12 g	Microscop y	USB	Eyepiece	Software included
TOUPCAM 8MP	8.3 Mp	sCMOS 1/2.5"	236 mV	2.72 x 4 cm	12 g	Microscop y	USB	Eyepiece	Software included