

# WET BENCH - 4 STUDENTS

References : LBPH4E01, LBPH4E02, LBPH4E03



**Prices include delivery excluding assembly and installation. For installation and connection, consult us.**

**24 colours of legs available**

Main Features:

PPH tank 300 x 300 x P190 (int)Frame

The supporting feet are made of square steel tube of 30 x 30 mm. They are equipped with levelling jacks with a floor mounting plate. The front and rear strips are made with a C-profile of 60 x 23 mm and ensure perfect flatness and rigidity of the worktop. All the metal elements constituting the frame are protected by a paint based on epoxy resin (23 colours available, see colour chart), cured and resistant to chemical attack. Fluid protection boxes and backsplashes are made of 19 mm thick white melamine.

Worktops

Compact laminate: self-supporting 16 mm, rot-proof phenolic resin covered with white melamine.

Sandstone: 8 mm thick matte white enamelled stoneware tile, sealed with cement on a 22 mm thick melamine-coated waterproof backing. The tiles are of 60 x 60 cm. dimensions The seals between the tiles are made of grey thermosetting antacid cement. The edges of the worktop are protected by a PVC edge preventing any impact on the edge of the tiles (protection of the glassware).

Enamelled glass: Tempered glass, 6 mm thick, enamelled on the underside, glued on a melamine-coated, 22 mm thick water-repellent backing.

Casings

Plumbing

- Outlet: tube with 40 mm female socket, connection at 200 mm from finished floor or podium.
- Cold water, hot water, gas: male stop valve 15/21, connection 300 mm from finished floor or podium.

Electricity  
230 V: 1 3 x 2.5 mm<sup>2</sup>. cable Length of connection 1.5.